DIVISION OF WATER APPROVED MATERIALS LIST (10/01/2022 VERSION) FOR USE ON NEW CONSTRUCTION OF POTABLE WATER FACILITIES

This form is part of the Approved Materials List that follows, and is intended for use by developers or contractors constructing potable water facilities within the City of Columbus and surrounding contracted Water Service Areas. An authorized representative of the developer or contractor shall check the box(es) on each item for materials to be used in conjunction with the project, shall fill out this form in its entirety, and shall sign the certification statement below. Please contact the Division of Water if part numbers or models indicated within the Approved Materials List are no longer available. Division of Water personnel will review this form and the Approved Materials List and will seperately attach review comments.

ne	
CONTRACTOR INFORMATION	SUPPLIER INFORMATION
Name of Contractor (Company)	Name of Supplier (Company)
Contact Person	Contact Person
Mailing Address	Mailing Address
City, State, Zip	City, State, Zip
Telephone	Telephone
Fax	Fax
E-Mail Address	E-Mail Address

I hereby certify that the specific products indicated within the attached Approved Materials List represent a true list of materials to be used within the project indicated above, and I acknowledge understanding of the requirements that follow. Any and all specific requirements detailed within the current version of the Columbus Construction and Material Specifications (CCMS) shall apply to all materials proposed for use on this project. When the notation "Full Submittal Required" or similar language appears within the Approved Materials List, or when required materials do not appear within this Approved Materials List, complete shop drawing submittals are required in accordance with the procedures detailed in the CCMS. All materials supplied to the job site shall conform in all ways to the requirements of the CCMS.

Signed By Contractor Representative

Printed Name of Contractor Representative

Date

Spec Section	Item	Description	Manufacturer	Size	Product No.	Selection	Comments
801	Pipe, Copper	For water mains 2-inch and smaller. All tubing shall be type K soft temper conforming to ASTM B 88 and in accordance with City of Columbus Construction and Materials Specifications. Material dimensions shall be copper tubing size (CTS).					Refer to approved copper tubing materials listed under Item 805.
801	Pipe, Ductile Iron	For water mains 3-inch and larger, manufactured per AWWA C151, and in	American Ductile Iron Pipe				Fastite Push-on, Mech. Joint & Flex-Ring restrained joint
		accordance with City of Columbus Construction and Materials Specifications.	McWane Ductile				Tyton Push-on, Mech. Joint & TR Flex restrained joint
			U.S. Pipe				Tyton Push-on, Mech. Joint & TR Flex or HDSS Restrained Joint Pipe
801	Pipe, Concrete	For water mains 20-inch and larger, manufactured per AWWA C301, in accordance with City of Columbus Construction and Materials Specifications. Full Submittal Required.	Thompson Pipe Group				Snap-Ring type joints to be used for all restrained joints
801	Pipe, Steel	For water mains 20-inch and larger, manufactured per AWWA M11, in accordance	American Spiral-Weld Steel Pipe				
		with City of Columbus Construction and Materials Specifications. Full Submittal	Northwest Pipe Co.				
		Required.	Thompson Pipe Group				
801	Pipe, PVC	For water mains 6-inch & 8-inch mains only, manufactured per AWWA C900, DR 14,	Diamond Plastics Corp.				
001	1 100,1 10	in accordance with City of Columbus Construction and Materials Specifications.	JM Eagle				
		Refer to CCMS Item 801 for restrictions on the use of PVC pipe.	National Pipe & Plastics				
			Westlake				
			IPEX				
801	Ductile Iron Fitting	Mechanical Joint (M.J) or Push-on Tees, for Water mains 3-inch and Larger,	American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
001	(Tee)	Manufactured per AWWA C110 / C111 / C153 and in accordance with City of	American Ductile Iron (ACIPCO) McWane Ductile				TR Flex Fittings for restrained joint pipe
	,	Columbus Construction and Materials Specifications.	Sigma				ווא ויפא ו יומוואס וטו ופטוומוווסט וטווג אואפ
			Sigma Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
			SIP Industries				TO Flav Fittle as for exclusional triat size
			US Pipe				TR Flex Fittings for restrained joint pipe
801	Ductile Iron Fitting	Mechanical joint or push-on swivel & anchoring tees, for water mains 3-inch and	US Pipe American Ductile Iron (ACIPCO)				Metalfit
001	(Swivel /Anchoring Tee) larger,	larger, manufactured per AWWA C110 / C111 / C153 and in accordance with City of Columbus Construction and Materials Specifications.	McWane Ductile Iron (ACIPCO)				
			Sigma				
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
801	Ductile Iron Fitting	Machanical joint or puch an arganas, for water mains 2 inch and larger	SIP Industries				Flex-Ring Fittings for restrained joint pipe
001	(Cross)	Mechanical joint or push-on crosses, for water mains 3-inch and larger, manufactured per AWWA C110 / C111 / C153 and in accordance with City of Columbus Construction and Materials Specifications.	American Ductile Iron (ACIPCO)				TR Flex Fittings for restrained joint pipe
	(01033)		McWane Ductile				TR Flex Fittings for restrained joint pipe
			Sigma				
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
			SIP Industries				TD Flav Filling for an initial sint sin a
			US Pipe				TR Flex Fittings for restrained joint pipe
801	Ductile Iron Citting	Mechanical joint or puch on 11 1/4 degree hands for water mains 0 inch and 1	US Pipe				Metalfit Elay Diag Eithings for restrained joint sing
001	Ductile Iron Fitting (11 1/4 Degree Bend)	Mechanical joint or push-on 11 1/4 degree bends, for water mains 3-inch and larger, manufactured per AWWA C110 / C111 / C153 and in accordance with City of	American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
	(11 1/4 Degree Derid)	Columbus Construction and Materials Specifications.	McWane Ductile				TR Flex Fittings for restrained joint pipe
			Sigma				
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
			SIP Industries				
			US Pipe				TR Flex Fittings for restrained joint pipe
			US Pipe				Metalfit
801	Ductile Iron Fitting	Mechanical joint or push-on 22 1/2 degree bends, for water mains 3-inch and larger,	American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
	(22 1/2 Degree Bend)	manufactured per AWWA C110 / C111 / C153 and in accordance with City of Columbus Construction and Materials Specifications.	McWane Ductile				TR Flex Fittings for restrained joint pipe
			Sigma				
			Star Pipe Products				

<u>.</u>		 	
	Tyler Union	C	
	United-NAPAC, Inc.	E	
	NACIP	C	
	SIP Industries	C	
	US Pipe	C	TR Flex Fittings for restrained joint pipe
	US Pipe	C	Metalfit

Spec Section	Item	Description	Manufacturer	Size	Product No.	Selection	Comments
801	Ductile Iron Fitting	Mechanical joint or push-on 45 degree bends, for water mains 3-inch and larger,	American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
(45	(45 Degree Bend)	manufactured per AWWA C110 / C111 / C153 and in accordance with City of	McWane Ductile				TR Flex Fittings for restrained joint pipe
		Columbus Construction and Materials Specifications.	Sigma				
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
			SIP Industries				
			US Pipe				TR Flex Fittings for restrained joint pipe
			US Pipe				Metalfit
801	Ductile Iron Fitting	Mechanical joint or push-on 90 degree bends, for water mains 3-inch and larger,	American Ductile Iron (ACIPCO)		1		Flex-Ring Fittings for restrained joint pipe
	(90 Degree Bend)	manufactured per AWWA C110 / C111 / C153 and in accordance with City of	McWane Ductile				TR Flex Fittings for restrained joint pipe
		Columbus Construction and Materials Specifications	Sigma				······································
			Star Pipe Products				
			Tyler Union		<u></u>		
			United-NAPAC, Inc.				
			NACIP		<u> </u>		
			SIP Industries		<u> </u>		
					<u> </u>		TP Elex Eittings for restrained joint ning
			US Pipe US Pipe		<u> </u>		TR Flex Fittings for restrained joint pipe Metalfit
801	Ductile Iron Fitting	Mechanical joint or push-on offset fitting. Permitted for use only on 6-inch diameter			ł		Ivietanit
001	(Offset)	fire bydrant loads Manufactured per AWWA C110 / C111 / C1E2 and in accordance	McWane Ductile		<u> </u>		
	(0001)	with City of Columbus Construction and Materials Specifications	Sigma		ł		
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
801		MJ solid sleeve full body fitting, for water mains 3-inch and larger, in accordance	SIP Industries		<u> </u>		
801	(Solid Sleeve - Long) W		American Ductile Iron (ACIPCO)		_		
		Standard Drawing L-7401	McWane Ductile				
1		с. С	Sigma		_		
			Star Pipe Products				
			Tyler Union				
1			United-NAPAC, Inc.				
			NACIP				
1			SIP Industries				
			US Pipe				TR Flex Fittings for restrained joint pipe
			US Pipe				Metalfit
801	Ductile Iron Fitting		American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
	(Reducer)	Columbus Construction and Materials Specifications	McWane Ductile				
			Sigma		l		
1			Star Pipe Products				
			Tyler Union		L		
			United-NAPAC, Inc.		L		
			NACIP		L		
1			SIP Industries		L		
1			US Pipe				TR Flex Fittings for restrained joint pipe
			US Pipe				Metalfit
801	Ductile Iron Fitting	Mechanical joint or push-on plugs, for water mains 3-inch and larger, manufactured	American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
	(Plug)	per AWWA C110 / C111 / C153 and in accordance with City of Columbus	McWane Ductile				TR Flex Fittings for restrained joint pipe
1		Construction and Materials Specifications.	Sigma				
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
1			SIP Industries				
			US Pipe				TR Flex Fittings for restrained joint pipe
			US Pipe				Metalfit
	1				·	_	

Spec Section	Item	Description	Manufacturer	Size	Product No.	Selection	Comments
801	Ductile Iron Fitting	Mechanical joint or push-on caps, for water mains 3-inch and larger, manufactured	American Ductile Iron (ACIPCO)				Flex-Ring Fittings for restrained joint pipe
	(Cap)	per AWWA C110 / C111 / C153 and in accordance with City of Columbus	McWane Ductile				TR Flex Fittings for restrained joint pipe
		Construction and Materials Specifications.	Sigma				
			Star Pipe Products				
			Tyler Union				
			United-NAPAC, Inc.				
			NACIP				
			SIP Industries				
			US Pipe				TR Flex Fittings for restrained joint pipe
			US Pipe				Metalfit
801	Mechanical Joint	Compact MJ X MJ adapter that allows MJ fitting bells (ie. tees & valves) to be restrained to one another with bolts, and in accordance with City of Columbus	Infact Corporation		Foster		
	Adaptor (Compact)	Construction and Materials Specifications.	Star Pipe Products		Series 100		
			US Pipe				Metalfit
801	Mechanical Joint Gland	Standard or compact mechanical joint gland, for water mains 3-inch and larger,	McWane Ductile				
		manufactured per AWWA C110 / C111 / C153 and in accordance with City of Columbus Construction and Materials Specifications.	Ferguson/Pro Select				
		Coumbus Construction and Materials Specifications.	Sigma				
			Star Pipe Products				
			Tyler Union	ļ			
			United-NAPAC, Inc.	ļ			
			NACIP				
			SIP Industries				
801	Gasket	Gaskets used at joints, for water mains 3-inch and larger, manufactured per AWWA C110 / C111 / C153 and in accordance with City of Columbus Construction and	McWane Ductile				
		Materials Specifications. No asbestos content.	Ferguson/Pro Select				
	Water		Sigma				
			Star Pipe Products				
			Tyler Union				
			SIP Industries				
801	leint Destreining Claude	Temporary joint restraint, for water mains 3-inch and larger, manufactured per	EGW Utilities Inc.		White Rhino		
801		AWWA C110 / C111 / C153 and C301, and in accordance with City of Columbus	EBBA Iron, Inc.		Megalug Series 1100		
	(remporary)	Construction and Materials Specifications.	Ford Meter Co.		Uni-Flange Series 1400		
		Permanent joint restraint for fire hydrant leads.	Romac Ind., Inc.		RomaGrip		
			Sigma Smith-Blair		One-Lok Series SLDE Cam-Lock Series 111		
			Star Pipe Products		Stargrip Series 3000		
			Tyler Union		TUFGrip Series 1000		
			SIP Industries		EZ Grip		
801	Factory-Coated Carbon	Nuts and bolts for installation of, fittings, mechanical joints, pipe restraint products,	Sigma		ТТВ		Blue Flourocarbon Tee Head Bolts and Nuts
	Steel nuts & bolts	etc.	Tyler Union	1	Cor-Blue T-bolts		Blue Flourocarbon Tee Head Bolts and Nuts
			Star Pipe Products	1	Star Blue		Blue Flouropolymer Tee Head Bolts and Nuts
			Ferguson/Pro Select	1	Core Blue		Blue Flouropolymer Tee Head Bolts and Nuts
			Birmingham Fastener, Inc.				Blue Flouropolymer Tee Head Bolts and Nuts
			SIP Industries	1			Blue Flouropolymer Tee Head Bolts and Nuts
			EGW Utilities Inc.		White Rhino		Blue Flourocarbon Tee Head Bolts and Nuts
801	Coupling				Style 38		18" & Larger Water Mains.
		Columbus Construction and Materials Specifications.	Romac Ind., Inc.		TC400		12" & Larger Water Mains.
			Ford Meter Co.		Ultra Flex		Extended Range (4"-12")
			Power Seal		Power Max		Extended Range (2"-12")
			Romac Ind., Inc.		Style XR 501		4" to 12" Water Mains
			Romac Ind., Inc.		"MACRO"		4" to 12" Water Mains
			Smith Blair		461 Series		2" to 12" Water Mains.
			Smith Blair		441 Series		2" to 16" Water Mains.
			Total Piping Solutions, Inc.		TX3		Extended Range (4"-12")
			Total Piping Solutions, Inc.		Hymax 2000 Series		2" to 12" Water Mains.
801	Polyethylene	8-mil. thick polyethylene encasement sleeve for ductile iron pipe (DIP) per AWWA	KMA Enterprises	I	"PET" Series		
	Encasement Tubing	C105.	Balcan Plastics Limited/First Film	1	V-Bio		
			Extruding or Crayex Corporation Sigma		V-DIU		
			Sigma T. Christy Enterprises, Inc.				
			AA Thread Seal Tape, Inc.	1			
	1	1	, st filleau Geal Tape, lilo.	L	1		

Spec Section	ltem	Description	Manufacturer	Size	Product No.	Selection	Comments
801	Polyethylene	1 1/2" wide, 6-mil. thick adhesive PVC outer wrap tape for underground applications.	KMA Enterprises				2" Wide Tape
	Encasement Tubing Tape		Sigma				
			T. Christy Enterprises, Inc.				
			AA Thread Seal Tape, Inc.				2" Wide Tape
801	Underground Corrosion	Corrosive protection for underground metal surfaces (bolts, restraint rodding, etc.)	Denso		"LT" Tape		Low Temperature Petrolatum Tape
	Protection-Metal	For aerosol undercoating products, follow manufacturer temperature restrictions for	Trenton		#1 Wax Tape		
	Surfaces	product application. For Black Gilsonite Asphalt Paint, keep product warm when	3M		08881		Underseal Rubberized Undercoating Black
		working in conditions below 32°F. Do not thin product with mineral spirits or other agents.	Permatex		80072 (117EA)		Undercoating - Aerosol coating
		agents.	Carquest		CCM 26903		Undercoating - Aerosol coating
			J.C. Whitlam Mfg. Co.		Black Dragon		Black Gilsonite Asphalt Paint
			Hercules Chemical Company		Black Magic		Black Gilsonite Asphalt Paint
801	Concrete Bonding	For cement mortar lining field repair on Steel Pipe, in accordance with City of	Larsen Products Corp.		"Weld-Crete"		
	Agent	Columbus Construction and Materials Specifications.					
		6" wide, Warning/Identification (Detectable) Marking Tape for buried facilities, blue in	Harris Industries, Inc.				
	Таре	color.	Pro-Line				
			ProPak				
			Sigma				
			T. Christy Enterprises, Inc.				
801	Poly Pig (Medium Density)	For use in Cleaning of New Water Mains 12-inch and larger, in accordance with City of Columbus Construction and Materials Specifications.	Pipeline Pigging Products		Model B4		
			Pipeline Pigging Products		Model RX4		
			Girard		Model RCC		
			Knapp		Model 1-C		
801	Chlorination Tap (B.O./Sampling Outlet)	For use in chlorinating newly installed water mains in accordance with AWWAC-651 along with City of Columbus Construction and Materials Specifications. Note that all taps are to be removed once chlorination is complete and shall be plugged with an approved brass plug.					Refer to approved corporation stop valves listed under Item 805.
				_			
801	Brass Plug	For use in plugging a water main once a corporation stop has been removed. Plug	A.Y. McDonald	_	73206		3/4" - 2"
		must have AWWA CC style threads.	Cambridge Brass	_	Model 98NL	—	3/4" - 2"
			Ford Meter Co.		CSP-NL		3/4" - 1"
			Mueller Co.		H-10033N		3/4" - 2"
801	Tracer Wire	12 GA AWG, solid copper HDPE jacket, or high strength HDPE jacket copper-clad	Copperhead Industires	_	1230B-HS		
		steel reinforced tracer wire, for use with PVC pipe.	Pro-Line Safety Products		Pro-Trace HF-CCS PE30		
801	Tracer Wire Grounding	1.5-lb, drive-in, magnesium rod with a minimum 20-feet, 12 AWG red HDPE	Copperhead Industires		ANO-12		
	Rod	insulated copper-clad steel wire connected to the rod.	Pro-Line Safety Products		Pro-Trace Ground Rod		
801	Tracer Wire Termination	Grade level / in-ground tracer wire access box with dual terminal lid.	Copperhead Industires		SnakePit LD14B2T-ADJ		
	Box		KrisTech		Test Station, 2-terminal cove		

Spec Section	Item	Description	Manufacturer	Size	Product No.	Selection	Comments
802	Valve, Butterfly	For water valves 20-inch and larger, manufactured per AWWA C504 and in	Henry Pratt Co.		Groundhog Series		20" & Larger
ļ		accordance with City of Columbus Construction and Materials Specifications.	DeZurik		BAW AWWA		20" & Larger
ł			Mueller		Lineseal		20" & Larger
802	Valve, Curb Stop	For valves on water mains 2-inch and smaller					Refer to approved curb stop valves listed under Item 805.
802	Valve, Resilient Seated	For water valves 3-inch to 16-inch, manufactured per AWWA C-500, C509 and C-	American Flow Control		Series 2500		
	Gate	515 and in accordance with City of Columbus Construction and Materials	American Flow Control		Series 2500 - Restrained		Alpha restrained joint ends, For 4" - 12" valves
ļ		Specifications.	American AVK		Series 45		
ļ			Clow Corporation		Model 2639/2640		For 3" - 12" Valves (M.J.) Type F-6100, Type F-6114 for Tapping
ļ			Clow Corporation		Model 2638		For 3" - 16" Valves (M.J.) Type F-6100, Type F-6114 for Tapping
ļ			East Jordan Iron Works		"FlowMaster"		For 4"- 16" Valves.
ļ			Kennedy Valve Company		"KS-FW"		Sizes 3" - 16"
ļ			Kennedy Valve Company		"KS-RW"		Sizes 3" - 12"
ļ			Mueller Co.		Series 2360		For 3"- 16" Valves.
ļ			Mueller Co.		Series T2360		For 3"- 16" Valves (Tapping)
802	Valve Box, ≤ 2" Valve	Screw type valve box for use on water valves 2-inch and smaller, outside traveled areas and in accordance with City of Columbus Construction and Materials Specifications Item 805.					Refer to approved curb boxes listed under Item 805.
	Valve Box, Standard	Screw type valve box for use on water valves 3-inch to 16-inch, not in a traveled	General Foundries Inc.		340C0		
ł	(Three Piece)	area, and in accordance with City of Columbus Construction and Materials	Bingham & Taylor		I5BC6W		
ļ		Specifications.	Sigma		VB630		
ļ			Star Pipe Products		VB-0005		
ļ			Tyler Union		6860		
			SIP Industries		6000 - 6020		
802	Valve Box, Heavy Duty	For use on any water valves 16-inch and larger, any 3-inch & larger valve within a traveled area, or any tapping valve, in accordance with City of Columbus Construction and Materials Specifications DOPW standard drawing L-6316A.	East Jordan Iron Works		449		Valve Box Assembly
ļ			General Foundries Inc.		COLVB		
ļ			Sigma		VB635		
ļ			Star Pipe Products		VB-0039		
802	Valve Box, Adjusting	For use on existing heavy duty valve boxes, in accordance with City of Columbus	SIP Industries American Highway Products, Ltd.		15VBXHDCL Columbus, Ohio		Pivoted Turnbuckle Expanding Linkage
	Ring	Construction and Materials Specifications DOPW Standard Drawing L-6316B.					
Spec Section	ltem	Description	Manufacturer	Size	Product No.	Selection	Comments
	Tapping Sleeve for CI,	Full body iron or fabricated steel tapping sleeve for 3" and larger wet taps on CI or D	American Flow Control		2800-C Series		4"x4" through 16"x12" (Ductile Iron, Cast Iron, or PVC)
	DI, and PVC Pipe	pipe in accordance with City of Columbus Construction and Materials Specifications.	Cascade		CST-EX		(Ductile Iron or PVC)
ļ	(Reduced Size Taps)		Cascade		CFT-ESS		(Ductile Iron or PVC)
ļ			Ford Meter Co.		FTSC		(Ductile Iron or PVC)
ļ			JCM Industries Inc.		JCM 412		6"x3" through 36"x12" (Ductile Iron or PVC)
ł			JCM Industries Inc.	L	JCM 432		4"x2" through 24"x8" (Ductile Iron, Cast Iron, or PVC)
ł			JCM Industries Inc.		JCM 452		(Ductile Iron or PVC)
ļ			Mueller Co.		H-615		4"x4" through 24"x24" (Ductile Iron, Cast Iron, or PVC)
I			Mueller Co.		H-616		4"x10" through 24"x24" (Cast Iron Only)
ļ			Powerseal		3490		(Ductile Iron, Cast Iron, or PVC)
I			Romac Ind., inc.		FTS420		(Ductile Iron or PVC)
ļ			Romac Ind., inc.		SSTIII		(Ductile Iron, Cast Iron, or PVC)
ł			Smith-Blair		622		4"x4" through 24"x12" (Ductile Iron or PVC)
			Smith-Blair		665		(Ductile Iron, Cast Iron, or PVC)
			Total Piping Solutions, Inc. Tyler Union	<u> </u>	Triple Tap		4" through 16" (Ductile Iron, Cast Iron, or PVC)
					25-U		6"x4" through 12"x12" (Ductile Iron, Cast Iron, or PVC) 4"x4" through 16"x12" (Ductile or Cast Iron)
902	Tanning Sloove for Cl	Iron tanning cleave (full body) for 2" and larger wet tans on CL or DL sins is					
803	Tapping Sleeve for Cl and DI Pine	Iron tapping sleeve (full body) for 3" and larger wet taps on CI or DI pipe in accordance with City of Columbus Construction and Materials Specifications.	American Flow Control		2800-C Series		
	and DI Pipe	Iron tapping sleeve (full body) for 3" and larger wet taps on CI or DI pipe in accordance with City of Columbus Construction and Materials Specifications.	American Flow Control Mueller Co.		H-615		4"x4" through 24"x24" (Ductile or Cast Iron)
			American Flow Control Mueller Co. Mueller Co.		H-615 H-616		4"x4" through 24"x24" (Ductile or Cast Iron) 4"x10" through 24"x24" (Cast Iron Only)
	and DI Pipe (Size-on-Size Taps)	accordance with City of Columbus Construction and Materials Specifications.	American Flow Control Mueller Co. Mueller Co. Tyler Union		H-615 H-616 25-U		4"x4" through 24"x24" (Ductile or Cast Iron) 4"x10" through 24"x24" (Cast Iron Only) 6"x4" through 12"x12" (Ductile or Cast Iron)
803	and DI Pipe (Size-on-Size Taps) Tapping Sleeve for	accordance with City of Columbus Construction and Materials Specifications. Fabricated steel tapping sleeve for 3" and larger wet taps on concrete pipe in	American Flow Control Mueller Co. Mueller Co. Tyler Union JCM Industries Inc.		H-615 H-616 25-U 415		4"x4" through 24"x24" (Ductile or Cast Iron) 4"x10" through 24"x24" (Cast Iron Only) 6"x4" through 12"x12" (Ductile or Cast Iron) Sized to fit actual OD of pipe, OD must
803	and DI Pipe (Size-on-Size Taps)	accordance with City of Columbus Construction and Materials Specifications.	American Flow Control Mueller Co. Mueller Co. Tyler Union		H-615 H-616 25-U		4"x4" through 24"x24" (Ductile or Cast Iron) 4"x10" through 24"x24" (Cast Iron Only) 6"x4" through 12"x12" (Ductile or Cast Iron)
803	and DI Pipe (Size-on-Size Taps) Tapping Sleeve for	accordance with City of Columbus Construction and Materials Specifications. Fabricated steel tapping sleeve for 3" and larger wet taps on concrete pipe in	American Flow Control Mueller Co. Mueller Co. Tyler Union JCM Industries Inc.		H-615 H-616 25-U 415		4"x4" through 24"x24" (Ductile or Cast Iron) 4"x10" through 24"x24" (Cast Iron Only) 6"x4" through 12"x12" (Ductile or Cast Iron) Sized to fit actual OD of pipe, OD must

Spec Section	Item	Description	Manufacturer	Size	Product No.	Selection	Comments
805	Corporation Stop	For water taps 2-inch and smaller, in accordance with City of Columbus Construction	A.Y. McDonald		74701BT		3/4" thru 2"
		and Materials Specifications. Dimensions shall be copper tubing size (CTS).	Cambridge Brass		Series 301NL		3/4" thru 2"
		Compression connection x AWWA taper thread. Pressure rated at 150 psi or higher.	Ford Meter Co.		"FB1000-QNL" Series		3/4" thru 2"
		Product must be certified to meet the requirements on NSF/ANSI 61. For water taps 3-inch and larger an approved tapping sleeve and valve shall be used for any hot-tap	Mueller Co.		B-25008N		3/4" thru 2"
		installation in accordance with Item 802.					
			Mueller Co.		H-15013N	_	For 1 1/2" & 2"
805	Curb Stop	For water taps 2-inch and smaller, in accordance with City of Columbus Construction	A.Y. McDonald		76100T		3/4" thru 2" Water Taps
	(Water Tap Valve)	and Materials Specifications. Dimensions shall be copper tubing size (CTS) with compression connections and pressure rated at 150 psi or higher. Product must be	Cambridge Brass		Series 202NL		3/4" thru 2" Water Taps
		certified to meet the requirements on NSF/ANSI 61. For water taps 3-inch and larger	Ford Meter Co.		"B44-NL" Series		3/4" thru 2" Water Taps
		an approved gate valve shall be used in accordance with Item 802.	Mueller Co.		B-25209N		3/4" thru 2" Water Taps
			Mueller Co.		H-15209N		3/4" thru 2" Water Taps
805	Curb Box, Standard	For curb stops 2-inch and smaller, in accordance with City of Columbus Construction	General Foundries Inc.		37094E		
		and Materials Specifications. For water taps 3-inch and larger an approved valve box shall be used in accordance with Item 802.	General Foundries Inc.		38094E		
		box snail be used in accordance with tieff 802.	Bingham & Taylor		I2B94EWOS		"New Style" lid acceptable
			Sigma		VB-794E		
			Star Pipe Products		SB94ES		
			Tyler Union		6500 Series		94-E
805	Copper Tubing	For water taps 2-inch and smaller, all tubing shall be type K soft temper conforming	Mueller Industries, Inc.		Type K Soft Copper		
		to ASTM B 88 and in accordance with City of Columbus Construction and Materials Specifications. Material dimensions shall be Copper Tubing Size (CTS). For water	Cambridge-Lee Industries, Inc.		Type K Soft Copper		
		taps 3-inch and larger an approved ductile iron pipe shall be used.	Cerro Flow Products, Inc.		Type K Soft Copper		
		aps 5-mon and raiger an approved ducine non pipe shair be used.	Great Lakes Copper, Inc.		Type K Soft Copper		
			Kessler		Type K Soft Copper		
			Wieland Coppoer Products, LLC		Type K Soft Copper		
805	Water Tap Saddle	For water taps 2-inch and smaller, where a hot tap is required, in accordance with	A.Y. McDonald		3801		For use on ex. IPS OD PVC pipe
		City of Columbus Construction and Materials Specifications. Material dimensions shall be copper tubing size (CTS). Provide single strap water tap saddles for 2-inch and smaller water mains. Provide double strap water tap saddles for 3-inch and larger water mains. For water taps 3-inch and larger, where a hot tap is required, an approved tapping sleeve shall be used in accordance with Item 802.	A.Y. McDonald		4835A		Single S.S. Strap
			A.Y. McDonald		4855A		Double S.S. Strap
			Cambridge Brass		Series 822		Single S.S. Strap
			Cambridge Brass		Series 812		Double S.S. Strap
			Ford Meter Co.		Style FS101		Single S.S. Strap
			Ford Meter Co.		Style FSD202		Double S.S. Strap
			JCM Industries Inc.		418		3/4" thru 1 1/2" Taps on 20" & Larger W.M.'s
			JCM Industries Inc.		425		3/4" thru 2" Taps on Conc. Steel Cylinder Pipe
			Mueller Co.		DR 1 S or BR 1 S		Single S.S. Strap
			Mueller Co.		DR 2 S or BR 2 S		Double S.S. Strap
			Romac Ind., inc.		101S or 101BS		Single S.S. Strap
			Romac Ind., inc.		202S or 202BS		Double S.S. Strap
			Smith-Blair		315 Series		Single S.S. Strap
			Smith-Blair	ļ	317 Series		Double S.S. Strap
805	Water Tap Tubing	For connecting to water tap tubing 2-inch and smaller, in accordance with City of	Cambridge Brass		Series 118NL		Copper to Copper (CTS to CTS)
	Couplings	Columbus Construction and Materials Specifications. Product must be certified to	Ford Meter Co.		Style C44-xx-Q-NL		Copper to Copper (CTS to CTS)
		meet the requirements on NSF/ANSI 61.	Mueller Co.		H-15403N		Copper to Copper (CTS to CTS)
			A.Y. McDonald		74758T and 74758Q		Copper to Copper (CTS to CTS)
			A.Y. McDonald		74756-CTS		Copper to Copper (CTS to CTS)
			A.Y. McDonald		Ranger Fittings		3/4" thru 1"
			Smith-Blair		411 w/ Adapter Gasket		Copper to Galvanized (CTS to IPS)
			Smith-Blair		525 w/ Adapter Gasket		Copper to Galvanized (CTS to IPS)
			Ford Meter Co.		C45-xx-G-NL		Copper to Galvanized (CTS to IPS)
805	Copper Disc	For abandoning water taps, placed at oulet of corporation stop in accordance with	Ford Meter Co.		Disc-x Style		3/4" thru 2"
		City of Columbus Construction and Materials Specifications. Material dimensions shall be copper tubing size (CTS).	Mueller Co.		H-15535		3/4" thru 2"
		אומו שב נסטטבו נעטוווע גובע (כדס).	A.Y. McDonald		6125		3/4" thru 1"

Spec Section	ltem	Description	Manufacturer	Size	Product No.	Selection	Comments
806	Casing Pipe	Steel casing pipe for protection/installation of water mains 6-inch and larger,	American Steel Pipe				
		manufactured per ASTM A-139 Grade B, in accordance with City of Columbus	Lally Pipe & Tube				
		Construction and Materials Specifications and DOPW standard drawing L-6324.	Northwest Pipe Co.				
			Arntzen Corporation				
			Pittsburgh	_			
806	Casing Spacers	Spacers used with casing pipe installations, in accordance with City of Columbus	Advanced Draduat & Customa	-	SI		
800	Casing Spacers	Construction and Materials Specifications and DOPW standard drawing L-6324.	Advanced Product & Systems		÷.		
			Pipeline Seal & Insulator, Inc.		C8G-2 or C12G-2		
			CCI		CSC	U	
806	Casing Pipe End Seals	City of Columbus Construction and Materials Specifications and DOPW standard	Advanced Product & Systems		Model AW		
			Pipeline Seal & Insulator, Inc.		Model W		
			CCI Piping System		Model ESW		
Spec Section	ltem	Description	Manufacturer	Size	Product No.	Selection	Comments
809	Fire Hydrant	For fire hydrant settings in accordance with City of Columbus Construction and	American Flow Control		Mark 73 Series		"No Drain" only
		Materials Specifications DOPW standard drawings L-6409, L-6637 and L-7601.	American Flow Control		Mark 73 -5		"No Drain" only. Alpha Joint Hydant Base for use on Mark 73 Series Hydrants
			Clow Corporation		Eddy F2641		
			Mueller Co.		Centurion		Super 200
Spec Section	Item	Description	Manufacturer	Size	Product No.	Selection	Comments
810	Hydrant Extension Kits	For vertically extending fire hydrant settings in accordance with City of Columbus	American Flow Control				
		Construction and Materials Specifications and DOPW standard drawings L-6409, L-	Clow Corporation				
		6637 and L-7601.	Mueller Co.				