



36' SECTION (RESIDENTIAL) COMBINATION CURB & GUTTER, TYPE STANDARD

CITY OF COLUMBUS, OHIO
DEPARTMENT OF PUBLIC SERVICE
DIVISION OF DESIGN AND CONSTRUCTION

STD DWG
2115
12/31/2018
SHT 1 OF 1

CITY ENGINEER

* SIDEWALK WIDTH PER STANDARD DRAWING 2300.

A MINIMUM 7 FT WIDE PEDESTRIAN ACCESS ROUTE (PAR) SHALL BE PROVIDED BETWEEN OPPOSING RAMPS AND SHALL HAVE A CROSS-SLOPE (THE LONGITUDINAL STREET SLOPE) NO GREATER THAN 1.56%.

SEE RESIDENTIAL STREET PAVEMENT DESIGN POLICY FOR PAVEMENT DESIGNS

COMBINATION CURB & GUTTER, TYPE STANDARD, PER STD DWG 2010

NO. 8 OR NO. 57 AGGREGATE
ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%

1.56%

3/8"

1/4" R.

NO. 8 OR NO. 57 AGGREGATE

ITEM 605 - 4" PIPE UNDERDRAIN

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

SUBGRADE

SLOPE: 4:1 OR FLATTER PREFERRED 3:1 MAX

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

UTILITY STRIP/TREE LAWN 3.13%
1'-0" MIN. AT 3.13%
1.56%

GRADING SECTION

PAVING SECTION

60'-0"

30'-0"

19'-0"

30'-0"

18'-0"

11'-0"

18"

18"

18"

12"

12"

12"

R/W

R/W

Q

1.56%

1.56%

1.56%