

SECTION SS-27

PROJECT IDENTIFICATION SIGNS

PART 1	GENERAL	
1.01	SUMMARY	
	A.	The Contractor shall provide all labor, materials, and equipment necessary to post project identification signs as required by this specification.
1.02	REFERENCES	
	A.	Reference Standards:
	1.	Standard Drawing AA-S175
1.03	DEFINITIONS	(Not Used)
1.04	SYSTEM DESCRIPTION	(Not Used)
1.05	SUBMITTALS	
	A.	The contractor shall submit detailed drawings of the proposed project identification signs and their support systems for approval prior to signage placement.
1.06	QUALITY ASSURANCE	(Not Used)
1.07	DELIVERY, STORAGE AND HANDLING	(Not Used)
1.08	PROJECT/SITE CONDITIONS	(Not Used)
1.09	SEQUENCING	(Not Used)
1.10	SCHEDULE	(Not Used)
1.11	WARRANTY	(Not Used)
1.12	SYSTEM STARTUP	(Not Used)
1.13	INSTRUCTION OF OWNER'S PERSONNEL	(Not Used)
1.14	COMMISSIONING	(Not Used)
1.15	MAINTENANCE	
	A.	Signs shall be maintained throughout duration of the construction so that they remain clean, legible and structurally sound. Any damages to said signs shall be repaired immediately, including

PART 2 PRODUCTS

2.01	MANUFACTURERS	(Not Used)
2.02	EXISTING PRODUCTS	(Not Used)

A. Signs may be constructed of either metal or wood and shall of be professional quality. If plywood is used, it must be ¾" exterior grade with mitered trim on all edges.

2.08 MIXES (Not Used)

B. Size: Signs shall be 30 inches high and 42 inches wide per standard drawing AA-S175, unless otherwise approved by the Engineer. On major roads wider than three lanes, in non-residential areas, larger sizes may be approved by the Engineer if deemed necessary for better visibility.

Utility Fee Type: xxxxx

A. Paint. Paint shall be exterior gloss enamel white base paint with black lettering.

2.11 SOURCE QUALITY CONTROL (Not Used)

PART 3 EXECUTION

3.01 ACCEPTABLE INSTALLERS (Not Used)

3.02 EXAMINATION (Not Used)

3.03 PREPARATION (Not Used)

3.04 ERECTION

A. Signs shall be installed one week prior to the construction start date.

B. Signs shall be removed one week after completion of project.

3.05 INSTALLATION

A. The contractor shall furnish and install project signs as follows:

1. Two (2) signs shall be provided at locations as directed by the Engineer. The Contractor shall coordinate location with Inspector and property owners.

2. Three (3) signs to be provided for the CIPP lining work. These signs will move with the Contractor. One sign will be provided at the launch manhole. One sign will be provided at the exit manhole. One sign will be provided in the area of the subsequent sewer to be lined.

B. Signs shall be installed along the public right of way, such as the city tree lawn area near the curb, where the signs would be visible to motorists.

C. Locations of the signs shall not block the visibility of stop signs, railroad crossings or other signage that might pose a public safety hazard

3.06 APPLICATION (Not Used)

3.07 CONSTRUCTION (Not Used)

3.08 REPAIR/RESTORATION (Not Used)

3.09 RE-INSTALLATION (Not Used)

3.10 FIELD QUALITY CONTROL (Not Used)

CIP #

SS-27 Project Identification Signs.docxName SS#-3

3.11	ADJUSTING	(Not Used)
3.12	CLEANING	(Not Used)
3.13	DEMONSTRATION	(Not Used)
3.14	PROTECTION	(Not Used)
3.15	SCHEDULES	(Not Used)

- A. Payment will be lump sum for the project identification sign required, as stated above.

<u>ITEM</u>	<u>UNIT</u>	<u>DESCRIPTION</u>
SS-27	LS	Project Identification Signs

END OF SECTION