



REPAIR DETAIL
NOT TO SCALE

NOTES:

1. BEDDING AND BACKFILL IN ACCORDANCE WITH CMSC ITEM 901 (SEE AA-S149 AND AA-S151). OPEN CUT REPAIRS WITHIN RIGHT OF WAY OR PAVEMENT SHALL USE COMPACTED GRANULAR BACKFILL, CMS ITEM 912.
2. CONTRACTOR SHALL ARRANGE FOR ACCESS TO POINT REPAIR LOCATION AND WORK WITHIN EXISTING EASEMENT.
3. CONTRACTOR SHALL VERIFY LOCATION AND LENGTH OF POINT REPAIR USING CCTV TAPES AND LOGS AND FIELD INVESTIGATIONS. THE UNIT PRICE OF POINT REPAIR SHALL INCLUDE ALL REMOVALS, ACTUAL REQUIRED LENGTH AT POINT REPAIR, AND ALL RESTORATION WORK. POINT REPAIR STATIONS SHOWN ON THE PLANS ARE APPROXIMATE.
4. PLASTIC TO PLASTIC REPAIRS SHALL REQUIRE A HARD FITTING. FOR ALL OTHER PIPE MATERIALS THE FITTINGS SHALL BE FROM THE CITY OF COLUMBUS APPROVED SUPPLIERS LIST.
5. CONCRETE ENCASEMENT SHALL NOT BE USED ON FLEXIBLE PIPE POINT REPAIRS UNLESS THE ENTIRE SEWER SEGMENT WAS PREVIOUSLY CONCRETE ENCASSED.

CITY OF COLUMBUS, OHIO
DEPARTMENT OF PUBLIC UTILITIES
DIVISION OF SEWERAGE & DRAINAGE

[Handwritten Signature]

SSS MANAGER

STANDARD DRAWING
AA-S170

REVISED 10/12/21

PAGE

1

1

OPEN CUT POINT
REPAIR DETAIL