

MIS #	DESCRIPTION
DOP REQUIREMENTS	
1	STREET LIGHT LOCKOUT/TAGOUT (LOTO)
2	GUIDELINES FOR INSPECTION & ACCEPTANCE OF STREET LIGHTING SYSTEMS
3	GUIDELINES FOR STREET LIGHTING "MATERIALS FOR APPROVAL" SUBMITTAL PACKAGES
4	INSPECTION CHECKLIST
MISCELLANEOUS	
50	PROJECT IDENTIFICATION SIGN
51	ANCHOR AND DOWN GUY ASSEMBLY, 10,000 LBS
52	POLE KEY ANCHOR ASSEMBLY
53	SPAN GUY ASSEMBLY WITH STUB
54	PULL BOX (13" H x 24" W x 18" D)
55	GROUND ROD (Wood Pole Installation Only)
56	RISER, STREET LIGHT CIRCUIT (No Controller)
57	METER SOCKET, 100 AMP FOR CITY OF COLUMBUS POWERED STREET LIGHTING CIRCUITS
58	MINIMUM TREE CLEARANCE FOR DOWNTOWN, URBAN, & RURAL AREAS
59	CT METER CABINET, 480 VOLT AEP POWERED STREET LIGHTING CIRCUITS
60	AEP POWER SERVICE FOR STREET LIGHTING
61	PULL BOX (17" H x 30" W x 24" D)
62	RISER, STREET LIGHT CIRCUIT FOR POLE MOUNT CONTROLLER
BRACKETS	
100	BRACKET, X' ALUMINUM, FOR WOOD POLE (6' OR 8')
101	BRACKET, X' ALUMINUM, FOR WOOD POLE (10', 12', OR 15')
102	BRACKET, 20' ALUMINUM, FOR WOOD POLE
103	BRACKET, 6' ALUMINUM, FOR WOOD POLE, TEAR DROP
104	BRACKET ASSEMBLY, TRAFFIC/LIGHT COMBINATION POLE, DOWNTOWN
FOUNDATIONS	
200	STREET LIGHT FOUNDATION, 4'
201	STREET LIGHT FOUNDATION, 6'
202	STREET LIGHT FOUNDATION, 8'
203	STREET LIGHT FOUNDATION, 6', DOWNTOWN
POLES	
300	POLE, ALUMINUM, X' BRACKET, T-BASE, 30' MOUNTING HEIGHT (6',8',10',12',15')
301	POLE, ALUMINUM, 10' BRACKET, T-BASE, 40' MOUNTING HEIGHT
302	POLE, ALUMINUM, X' BRACKET, T-BASE, 40' MOUNTING HEIGHT (12',15')
303	POLE, ALUMINUM, X' BRACKET, T-BASE, 30' MOUNTING HEIGHT, BRONZE (8',10,12)
304	POLE, ALUMINUM, X' BRACKET, T-BASE, 40' MOUNTING HEIGHT, BRONZE (10',15')
305	POLE, ALUMINUM, 6' BRACKET, T-BASE, 31' MOUNTING HEIGHT, BLACK/GREEN (TEARDROP)
306	POLE, ALUMINUM, LOW MAST, ADJUSTABLE 39' TO 43'
307	POLE, FIBERGLASS, DECORATIVE 11'-6"
308	POLE, DOWNTOWN
309	POLE, ALUMINUM, 14" TENON, T-BASE, 40' MOUNTING HEIGHT
310	POLE, WOODEN

311	POLE FIBERGLASS. DECORATIVE 13'
312	POLE, ALUMINUM, 14" TENON, T-BASE, 30' MOUNTING HEIGHT
	CIRCUITS
400	OVERHEAD CIRCUIT, "X" WIRE-OPEN WIRE (2, 3, OR 4 WIRE)
401	OVERHEAD CIRCUIT, 2 WIRE-#2 DUPLEX
402	OVERHEAD CIRCUIT, 2 WIRE-#6 DUPLEX
403	UNDERGROUND CIRCUIT, 2 WIRE
404	UNDERGROUND CIRCUIT, 3 WIRE
	WIRING
500	POLE TO BE WIRED, 2-WIRE
501	POLE TO BE WIRED, 3 WIRE
	CONTROLLERS
600	CONTROLLER, 2 WIRE, 480V, POLE MOUNT
601	CONTROLLER, 2 WIRE, 480V, PAD MOUNT
602	CONTROLLER, 2 WIRE, 480V, PEDESTAL MOUNT
603	CONTROLLER, 3 WIRE, 480V, PAD MOUNT
604	CONTROLLER, 3 WIRE, 480V, PEDESTAL MOUNT
	CONDUIT
700	2" CONDUIT, CONCRETE ENCASED
701	2" CONDUIT-JACKING, DRILLING, OR PUSHING
702	3" RIGID STEEL WITH 2" CONDUIT INSERT
703	2.5" HDPE CONDUIT WITH 1-1/2" CABLE-IN-DUCT
704	CABLE-IN-DUCT, 1-1/2", TRENCHLESS INSTALLATION, 2 WIRE
705	CABLE-IN-DUCT, 1-1/2", TRENCHLESS INSTALLATION, 3 WIRE
706	CONDUIT REPAIR/EXTENSION, CONDUCTORS REPLACED
707	CONDUIT REPAIR/EXTENSION, CONDUCTORS INTACT
	LUMINAIRES
800	LUMINAIRE, LED, COBRA HEAD
801	LUMINAIRE, LED, TEARDROP
802	LUMINAIRE, LED, ACORN
803	LUMINAIRE, LED, TRADITIONAL
804	LUMINAIRE, LED, UNDERPASS
805	LUMINAIRE, LED, SQUARE
806	LUMINAIRE, LED, LOW MAST
	REMOVALS
900	FOUNDATION REMOVAL
901	EXISTING OVERHEAD SYSTEM REMOVAL
902	EXISTING UNDERGROUND SYSTEM REMOVAL

Revised 12/7/2023